



Cyanlite™
LED Panel Lights
SAGITTA
for
Surface Mounted
Installation



160



210





310



610/630





Overview

The Cyanlite™ backlite LED panel lights SAGITTA series has been designed specifically for Surface Mounted installation on Plasterboard and Concrete ceilings. The Sagitta series surface mounted luminaires have a wide product portfolio includes square and rectangular shape. The default housing is in WHITE, other finishing as BLACK and SILVER are optional.

With Cyanlite patented mounting fixture, the installer no need to make the positioning when install, so the installation is simple and easy, also no need to dismantle and reassemble as traditional surface mounted luminaires, saving huge time for installers and enabling them to complete the project easily and quickly.

Advantages

- Specifically designed for surface mounted installation
- Backlite technology makes the product cost more competitive
- No Distance between ceiling and luminaire, no dust accumulation
- No screws visible for an elegant and high-end appearance
- Easy and fast installation, saving installation cost

Features

- Standard Models: 600x600, 625x625; 150x625, 150x1200, 150x1500; 200x1200, 200x1500; 300x1200, 300x1500; other customized sizes accepted.
- White (WH) RAL9016 as standard coating color, Black (BK), Silver (SI) and other RAL colors available on request
- System Efficiency up to 150 lm/W
- EN 12464-1& LG7 Compliant, UGR<19 Optional when fitted with Micro Prismatic diffuser
- Range of color temperatures 3000K, 3500K, 4000K, 5000K & 6500K
- 5 Years Warranty
- Various dimming options, including 0-10V, DALI, Switch Dim etc.
- Emergency options available


Specifications




| Model | Part No. | Power | Luminous Flux | Dimension (mm) |
|----------|------------|-------|---------------|----------------|
| 600x600 | SM30W060SA | 30W | 4500 lm | 610x610x50 |
| 625x625 | SM30W062SA | 30W | 4500 lm | 630x630x50 |
| 150x625 | SM20W106SA | 20W | 2800 lm | 160x630x50 |
| 150x1200 | SM30W112SA | 30W | 4200 lm | 160x1210x50 |
| 150x1500 | SM40W115SA | 40W | 5600 lm | 160x1510x50 |
| 200x1200 | SM30W212SA | 30W | 4200 lm | 210x1210x50 |
| 200x1500 | SM40W215SA | 40W | 5600 lm | 210x1510x50 |
| 300x1200 | SM30W312SA | 30W | 4200 lm | 310x1210x50 |
| 300x1500 | SM40W315SA | 40W | 5600 lm | 310x1510x50 |

*Other Spec/Power/Lumen/Size customizations are welcome.

Photometric




- UGR22 with Opalic Diffuser












- UGR19 with Micro Prismatic Diffuser

Dimensions (mm)



Cyanlite Sagitta Surface Mounted Series
Unit: mm






Installation



| | |
|---------------------|--|
| Efficacy | Upto 150 lm/W @ 4000K |
| CRI (Ra) | >80 (>90 Optional) |
| Color Temp. | 3000K/3500K/4000K/5000K/6000K or 3000K-4000K-6500K SCCT (Switchable CCT) |
| Lighting Method | Back-lite |
| Light Source | SMD2835 |
| SDCM | <3 |
| Beam Angel | 110° Opalic Diffuser/ 90° Micro Prismatic Diffuser |
| Service Life | L80B10 (25°C) > 50.000h |
| IP Rating | IP40 |
| Impact Resistance | IK04 |
| Hot Wire Resistance | 650°C |
| Driver | Flicker Free On/off driver as standard |
| Dimmable | 1-10V, DALI, Push Dim, Bluetooth Optional |
| Nominal Frequency | 50/60Hz |
| Power Factor | >0.9 |
| Input Voltage | 200~240V |
| Flick Free | Yes |
| Housing Color | RAL9016 White as standard, Black and Silver optional |
| Housing Material | Aluminum frame, Steel housing |
| LENS Material | Acrylic (PMMA) |
| Diffuser Material | Polystyrene (PS) |
| Storage Temp. | -40°C~+80°C |
| Working Temp. | -20°C~+45°C |
| Mount | Surface Mounted |
| Package | 1pcs per gift box, 4pcs per master box |
| Warranty | 5 years |

According to the International Standard of LED luminaire, here Cyanlite formally claims this product is only allowed to be applied to indoor environment. Meanwhile Cyanlite promises full warranty for the products. Any severe environment application including high/low temperature, high humidity, high salinity, high ammonia etc. is not permitted without the official confirmation from the manufacturer. If any misapplication happens, the warranty policy is no longer guaranteed. All values are typical values measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Rev: 1.2 2024/12



Cyanlite™
LED Luminaires
For
Recessed
• **Surface Mounted**
Suspended
Wall Mounted
Standing & Desktop
Installations

www.cyanlite.com

